

NTN, Timken, SKF, LYC Spherical Roller Bearing

内径 dmm	外径 Dmm	宽度 Bmm	NTN		Timken P68		SKF		LYC		Life		
			Basic Dynamic Load Rating (kN)	Basic Static Load Rating (kN)	Basic Dynamic Load Rating (kN)	Basic Static Load Rating (kN)	Basic Dynamic Load Rating (kN)	Basic Static Load Rating (kN)	Basic Dynamic Load Rating (kN)	Basic Static Load Rating (kN)	(NTN/LYC) ^(10/3)	(Timken/LYC) ^(10/3)	(SKF/LYC) ^(10/3)
25	52	18	57.5	46.1	50.6	43.1	49.9	44	36.1	36.6	4.72	3.08	2.94
30	62	20	75.7	64.5	67.4	60.8	66.1	60	51.7	55	3.56	2.42	2.27
35	72	23	100	92	90.5	88	88.8	85	68.9	72.5	3.46	2.48	2.33
40	80	23	116	105	104	99.7	98.5	90	86.9	93.9	2.62	1.82	1.52
	90	33	169	152	155	147	115	140	123	133	2.88	2.16	0.80
45	85	23	121	113	104	101	104	98	86.7	101	3.04	1.83	1.83
	100	36	206	187	190	182	190	183	141	154	3.54	2.70	2.70
50	90	23	130	124	117	118	107	108	90.3	97	3.37	2.37	1.76
	110	40	250	232	238	241	159	166	176	193	3.22	2.73	0.71
55	100	25	155	148	134	134	129	127	109	130	3.23	1.99	1.75
	120	43	296	274	266	265	280	280	210	243	3.14	2.20	2.61
60	110	28	187	181	169	174	159	166	129	158	3.45	2.46	2.01
	130	46	340	319	306	307	325	335	233	260	3.52	2.48	3.03
65	120	31	226	224	206	216	198	216	144	178	4.49	3.30	2.89
	140	48	369	343	344	346	357	360	285	315	2.37	1.87	2.12
70	125	31	235	240	216	231	213	228	163	207	3.39	2.56	2.44
	150	51	420	396	395	414	413	430	306	370	2.87	2.34	2.72
75	130	31	244	249	222	240	217	240	162	212	3.92	2.86	2.65
	160	55	491	467	450	478	462	475	350	427	3.09	2.31	2.52
80	140	33	278	287	254	278	243	270	187	248	3.75	2.78	2.39
	170	58	541	522	499	534	516	530	400	504	2.74	2.09	2.34
85	150	36	324	330	297	320	291	325	204	262	4.67	3.50	3.27
	180	60	599	604	543	584	577	620	426	512	3.11	2.25	2.75
90	160	40	384	398	355	388	331	375	257	340	3.81	2.94	2.32
	160	52.4	467	513	436	521	372	440	305	434	4.14	3.29	1.94
	190	64	668	652	606	659	637	695	475	583	3.12	2.25	2.66

NTN, Timken, SKF, LYC Spherical Roller Bearing

内径 dmm	外径 Dmm	宽度 Bmm	NTN		Timken P68		SKF		LYC		Life		
			Basic Dynamic Load Rating (kN)	Basic Static Load Rating (kN)	Basic Dynamic Load Rating (kN)	Basic Static Load Rating (kN)	Basic Dynamic Load Rating (kN)	Basic Static Load Rating (kN)	Basic Dynamic Load Rating (kN)	Basic Static Load Rating (kN)	(NTN/LYC) ^(10/3)	(Timken/LYC) ^(10/3)	(SKF/LYC) ^(10/3)
95	170	43	416	417	385	441	393	450	284	380	3.57	2.76	2.95
	200	67	732	751	663	725	699	765	509	617	3.36	2.41	2.88
100	165	52	464	563	446	583	385	490					
	180	60.3	586	661	554	678	498	600	420	605	3.04	2.52	1.76
	215	73	827	844	804	910	847	950	623	792	2.57	2.34	2.78
110	170	45	417	517	391	534	326	440	293	465	3.24	2.62	1.43
	180	69	622	769	595	811	540	750	483	754	2.32	2.00	1.45
	200	53	602	643	555	653	579	640	426	588	3.17	2.42	2.78
	240	69.8	975	972	710	887	627	765	515	760	8.39	2.92	1.93
120	180	60	526	726	523	762	456	670	395	686	2.60	2.55	1.61
	200	80	756	991	778	1080	679	950	561	919	2.70	2.97	1.89
	215	76	857	998	824	1040	734	910	595	910	3.37	2.96	2.01
	260	86	1170	1280	1080	1210	1019	1120	842	1110	2.99	2.29	1.89
130	200	69	682	936	664	966	569	815					
	210	80	803	1080	798	1130	701	1000	581	982	2.94	2.88	1.87
	230	80	958	1130	915	1170	826	1060	700	1080	2.85	2.44	1.74
	280	93	1330	1400	1250	1410	1178	1320	836	1090	4.70	3.82	3.14
140	210	69	709	990	702	1060	600	900	530	910	2.64	2.55	1.51
	225	85	951	1280	894	1290	797	1160	649	1120	3.57	2.91	1.98
	250	88	1140	1370	1090	1410	962	1250	835	1300	2.82	2.43	1.60
	300	102	1540	1720	1450	1670	1359	1560	1100	1420	3.07	2.51	2.02
150	225	56	798	1140	621	911	531	750	407	725	9.43	4.09	2.43
	250	100	1180	1590	1180	1680	1054	1530	951	1570	2.05	2.05	1.41
	270	96	1340	1620	1270	1660	1132	1460	907	1350	3.67	3.07	2.09
	320	108	1740	1890	1620	1890	1539	1760	1210	1660	3.36	2.65	2.23

NTN, Timken, SKF, LYC Spherical Roller Bearing

内径 dmm	外径 Dmm	宽度 Bmm	NTN		Timken P68		SKF		LYC		Life		
			Basic Dynamic Load Rating (kN)	Basic Static Load Rating (kN)	Basic Dynamic Load Rating (kN)	Basic Static Load Rating (kN)	Basic Dynamic Load Rating (kN)	Basic Static Load Rating (kN)	Basic Dynamic Load Rating (kN)	Basic Static Load Rating (kN)	(NTN/LYC) ^(10/3)	(Timken/LYC) ^(10/3)	(SKF/LYC) ^(10/3)
160	220	45	455	683	521	654							
	240	80	901	1290	914	1410	783	1200	660	1220	2.82	2.96	1.77
	270	109	1360	1860	1390	2000	1229	1760	1070	1750	2.22	2.39	1.59
	290	104	1550	1890	1470	1940	1281	1660	1020	1550	4.03	3.38	2.14
	340	114	1950	2210	1180	2110	1680	1960	1340	1840	3.49	0.65	2.12
170	230	45	468	723	453	716							
	260	90	1100	1600	1030	1570	963	1460	778	1310	3.17	2.55	2.04
	280	109	1410	1990	1440	2110	1270	1860					
	310	110	1700	2070	1660	2200	1472	1930	1200	1900	3.19	2.95	1.98
	360	120	2200	2630	2000	2360	1863	2160	1500	2140	3.58	2.61	2.06
180	250	52	573	869	572	907	519	830					
	280	100	1310	1880	1320	2040	1134	1730	930	1610	3.13	3.21	1.94
	300	118	1660	2290	1650	2450	1449	2160	1170	1930	3.21	3.15	2.04
	320	112	1800	2270	1720	2290	1557	2120	1310	2090	2.88	2.48	1.78
	380	126	2420	2810	3190	2600	2077	2450	1650	2330	3.58	9.00	2.15
190	260	52	603	935	589	964	499	800					
	290	100	1360	2000	1330	2100	1164	1800	938	1690	3.45	3.20	2.05
	320	128	1900	2700	1870	2760	1152	2500	1290	2250	3.64	3.45	0.69
	340	120	1990	2480	1940	2610	1759	2400	1490	2380	2.62	2.41	1.74
	400	132	2600	3120	2380	2830	2232	2650	1850	2590	3.11	2.32	1.87
200	280	60	766	1190	712	1130	651	1040					
	310	109	1570	2280	1560	2460	1353	2120					
	340	140	2130	2930	2030	2930	1865	2800	1530	2620	3.01	2.57	1.93
	360	128	2250	2840	2140	2890	1950	2700	1490	2370	3.95	3.34	2.45
	420	138	2830	3530	2470	2930	2439	2900					

NTN, Timken, SKF, LYC Spherical Roller Bearing

内径 dmm	外径 Dmm	宽度 Bmm	NTN		Timken P68		SKF		LYC		Life		
			Basic Dynamic Load Rating (kN)	Basic Static Load Rating (kN)	Basic Dynamic Load Rating (kN)	Basic Static Load Rating (kN)	Basic Dynamic Load Rating (kN)	Basic Static Load Rating (kN)	Basic Dynamic Load Rating (kN)	Basic Static Load Rating (kN)	(NTN/LYC) ^(10/3)	(Timken/LYC) ^(10/3)	(SKF/LYC) ^(10/3)
220	300	60	789	1260	739	1210	661	1080					
	340	118	1850	2720	1720	2720	1628	2600					
	370	150	2540	3620	2250	3220	2197	3350	1870	3350	2.78	1.85	1.71
	400	144	2890	3830	2490	3350	2485	3450	1860	3100	4.34	2.64	2.63
240	320	60	815	1350	785	1340	685	1160	579	1220	3.13	2.76	1.75
	360	118	1940	2980	1790	2900	1663	2700	1320	2610	3.61	2.76	2.16
	400	160	2910	4290	2690	4050	3042	4300	1980	3710	3.61	2.78	4.18
260	360	75	1130	1940	1120	1860	1050	1800	883	1760	2.28	2.21	1.78
	400	140	2520	3820	2380	3840	2135	3450	1700	3260	3.71	3.07	2.14
280	380	75	1180	2050	1170	1990	1016	1760	911	1860	2.37	2.30	1.44
	420	140	2620	4060	2420	4090	2248	3800					